



Transmitters and Flow Meters



pHT-5431

pH transmitter. Automatic or manual calibration. Output 4 – 20mA. Displays pH or mV. pH range 0 – 14. Temperature range 0 - 99°C. Waterproof panel and LCD digital display.



CT-121

Conductivity transmitter. Surface SMT technology. 316L/Ti metal electrode. Double line transmission. Output 4 – 20mA. Conductivity range: 0 – 20.0uS/cm, 0 – 200.0uS/cm, 0 – 2000uS/cm.



DBY-5600

Explosion-proof conductivity transmitter. For use in flammable/explosive gas environments. Output 4 – 20mA. Conductivity ranges: 0 – 20.0uS/cm, 0 – 200.0uS/cm; 0 – 20.0uS/cm, 0 – 200.0uS/cm, 0 – 2000uS/cm; 0 – 200.0uS/cm, 0 – 2000uS/cm, 0 – 20mS/cm.



DBY-5100 / 5200(shown)

Conductivity controller. Can be used as a meter and/or transmitter. Remote measurement. IP65 rated housings. 4-20mA isolated current output. 3.5 bit LCD digital display. Conductivity ranges: 0 – 20.0uS/cm, 0 – 200.0uS/cm; 0 – 20.0uS/cm, 0 – 200.0uS/cm, 0 – 2000uS/cm; 0 – 200.0uS/cm, 0 – 2000uS/cm, 0 – 20mS/cm. Temperature measurement range 0 - 50°C. Pipeline installation available (5100 model).



HL-360

Loop meter. Displays and controls conductivity, resistivity and pH. Used in off-site control rooms. High limit alarm. Output 4 – 20mA. Conductivity ranges: 0 – 20.0uS/cm, 0 – 200.0uS/cm, 0 – 2000uS/cm; 0 – 20.0mS/cm, 0 – 200.0mS/cm, 0 – 2000mS/cm. Resistivity range: 0 – 20.0Mohm/cm. pH range: 0 – 14.



WLG-8350 Series

Series of network flow meters. Recording capacity 4MB. Input signal type: pulse. Two channel OC output. Output 4 – 20mA, 0-10mA, 0-20mA (switchable). Various options on each model, such as RS485 communication, disk connections. Please enquire for further details.

Contact us for further information and pricing.

Ecotech Hydro. P.O.Box 350 Knysna 6570 Western Cape South Africa.

Phone: +27 (0)44 388 4896. Fax: +27 (0)86 612 9260. E-mail: info@ecotechhydro.com Web: www.ecotechhydro.com